# HSD Connector (Die casting type) CAM-K23HN/HR/LRS, CAM-K73LN, CAM-K23SN

Connectors

### FEATURES

- 1. Capable of high speed data transmission such as USB2.0, LVDS, and Ethernet, etc.
- 2. Include a die casting body (shell) that can contribute to the robust structure.
- 3. Selectable variations of mounting requirements. (Right angle / Straight / Standard / Low height)
- 4. Each coding (mating key) is available.
- 5. Compatible with Pin-in-Paste.
- 6. Compliant with RoHS Directive.



CAM-K73LN

CAM-K23SN

## HOW TO ORDER

#### 1. CAM-K23HN/HR/LRS

# $\frac{K23}{1} - \frac{004}{2} - 230 - ANAAA - \square_{3}$

- 1 Series No. (K23HN/HR/LRS)
- 2 No. of contacts (004 : 4pins)
- 3 Coding (A to F, Z / G to M, P)

3. CAM-K23SN

# <u>K23SN</u> - <u>004</u> - 230 - ANAAA - $\square_{3}$

- 1 Series No. (K23SN)
- 2 No. of contacts (004 : 4pins)
- 3 Coding (A to F, Z / G to M, P)

### 2. CAM-K73LN

$$\frac{K73}{1} - \frac{004}{2} - 230 - ANBAA - \square_{3}$$

- 1 Series No. (K73LN)
- 2 No. of contacts (004 : 4pins)
- 3 Coding (A to F, Z)

### HSD Connector (Die casting type)

### SPECIFICATIONS

#### **ELECTRICAL CHARACTERISTICS**

Rated Voltage	100V DC	
Rated Current	1.5A DC	
Characteristic Impedance	100Ω	
Insertion Loss	≦0.1dB to 1GHz	
Return Loss	≤-20dB to 1GHz ≤-17dB to 2GHz	

#### MECHANICAL CHARACTERISTICS


Life (Mating Cycle)	25 times
Total Insertion Force	≦30N
Total Withdrawal Force	5N to 30N


### **MATERIAL & FINISH**


Corr	ponent Parts	Material	Finish
CAM-K23 HN/HR/LRS Straight	Signal Pin	Copper alloy	Gold selective plating
	Housing	LCP resin	Black
	Shell	Zinc alloy	Ni plating
	Cover	PBT resin	Corresponds to each coding
CAM-K73LN Right Angle Low height	Signal Pin	Copper alloy	Gold selective plating
	Housing	PA resin	Black
	Shell	Zinc alloy	Ni plating
	Cover	PBT resin	Corresponds to each coding
	Lid	Copper alloy	Ni plating
CAM-K23SN Straight	Signal Pin	Copper alloy	Gold selective plating
	Housing	LCP resin	Black
	Shell	Zinc alloy	Ni plating
	Cover	PBT resin	Corresponds to each coding

### DIMENSIONS


CAM-K23HN














12







(19.9)

17.65


φ1.4

φ1

ŝ


2

7







Unit : mm





### HSD Connector (Die casting type)


#### CAM-K23LRS
















CAM-K73LN














Unit : mm

### HSD Connector (Die casting type)

CAM-K23SN







Any products mentioned in this catalog are subject to any modification in their appearance and others for improvements without prior notification.
The details listed here are not a guarantee of the individual products at the time of ordering. When using the products, you will be asked to check their specifications.

0.35 2.6

4–0.6