


# Rectangular Connectors IAM-H73, CAM-H74

## FEATURES

1. This series of connectors is used for the external connections between units. CAM-H74 series connectors are the surface mounting type connectors and IAM-H73 series connectors are the L type plugs.
2. This series of connectors has a power supply pins (6 pins).
3. This series of connectors has a coupling key, so there is no risk of miscoupling when using the same connector for multiple connections.
4. With the implementation of SMT, the GND through hole and terminals can have high peel strength.



Plug cable is customized based on your request and power line specification. Please let us know if you want to know the minimum order quantity.

## HOW TO ORDER

### 1. IAM-H73 (Cable Plug)

**H73-034-A006-A**  
 $\frac{1}{1} \frac{2}{2}$

- 1 Series No. (H73)
- 2 No. of contacts (034 : 34pins)

### 2. CAM-H74 (Socket)

**H74-034-050-AAGAA-A**  
 $\frac{1}{1} \frac{2}{2}$

- 1 Series No. (H74)
- 2 No. of contacts (034 : 34pins)

## SPECIFICATIONS

### ELECTRICAL CHARACTERISTICS

Rated Voltage	30V DC
Rated Current	Signal pin : 0.5A, Power Supply : 1.5A (6pins)
Withstanding Voltage	100V AC 1minute
Insulation Resistance	10MΩ min. (at 500V DC)
Contact Resistance	100mΩ max.

### MECHANICAL CHARACTERISTICS

Life (Matching Cycle)	5,000times
Total Insertion Force	40N (4kgf) max.
Total Withdrawal Force	1~40N (0.1~4kgf) max.
Using Temperature Range	-30~+85°C

