

Card Type Infrared Remote Control Unit **REA-16 (STD-16)**

OUTLINE

A model functioning as a space saver (thickness : only 7.5mm) with the maximum number of keys : 12. Here and there applied has been much contrivance in order not to allow reduced operability with functionally arranged, rather large switches into a narrow space and the geometrical form of body which familiarizes with our hands.

A wide variety of use range from TV to audio equipment has been ensured as such.

A high operational performance.



FEATURES

1. The setting of key number and nameplate design can be freely selected. (max. 12keys.)
2. It can be used for various applications.
3. Products : CHINA

SPECIFICATIONS

Power Supply	3V DC (CR2025 lithium battery 1 piece.)
Transmitting Signal Modulation Frequency	37.9kHz
Transmitting Distance	5m (min.)
No. of Keys	12keys (max.)
Operating Temperature Range	0~55°C
Transmitting IC	Individual orders

APPEARANCE AND OTHER SPECIFICATIONS

Item	Standard Specifications	Optional Specifications
Cases	Molded base color (black)	_____
Nameplate	Polyester (Design is individual specifications.)	_____
Back Label	None	Back label is available.
Infrared LED	1 piece	_____
Display LED	None	_____
Packing	Mitsumi standard packing.	A previous arrangement specially.

DIMENSIONS

