

24 Keys Infrared Remote Control Unit REA-22 (STD-22)

OUTLINE

This unit has been developed by refining Model REA-17 having max. 24 setting keys. It is characterized with switches being functionally arranged in a limited space, an easy-to-manipulate body profile, and easy operation. It is applicable over extensive fields, such as TV, VCR, audio units, etc. It has realized high operation performance.



FEATURES

1. The setting of key number and nameplate design can be freely selected. (max. 24keys.)
2. It can be used for various applications.
3. Can be available with a window.
4. Products : MALAYSIA · CHINA

SPECIFICATIONS

Power Supply	3V DC (SUM-3 dry battery 2pcs.)
Transmitting Signal Modulation Frequency	37.9kHz
Transmitting Distance	8m (min.)
No. of Keys	24keys (max.)
Operating Temperature Range	0~55°C
Transmitting IC	Individual orders

APPEARANCE AND OTHER SPECIFICATIONS

Item	Standard Specifications	Optional Specifications
Upper and Lower Cases	Molded base color (black)	Silk-screen printing is also possible at option.
Key Top	Monochrome, rubber-coated resin.	Plural-color is available at option.
Window (LED part)	None	Can be available for attachment.
Nameplate	Polyvinylchloride (Design is individual specifications.)	Polystyrene and polycarbonate is also possible at option. (Design is individual specification.)
Back Label	None	Back label is available.
Infrared LED	1 piece	_____
Packing	Mitsumi standard packing	A previous arrangement specially.

DIMENSIONS

