

# Card Type Infrared Remote Control Unit REA-36 (STD-36)

## OUTLINE

This space-saving model is only 9mm thin, but even so a maximum of 14 keys can be set. There are many features that enhance user-friendliness, such as the large switches arranged functionally within a small space and the comfortable shape. Also, the rubber switches offer a higher level of operability than those on conventional card remote controls. This model also has the same wide range of use, from video cameras and car audio to portable AV equipment. It realizes a high degree of operation performance.



## FEATURES

1. Key settings (maximum 14 keys) and nameplate design can be custom ordered.
2. Can be used with video cameras, car audio, portable AV equipment and more.
3. Manufacturing location: Malaysia.

## SPECIFICATIONS

Power Supply	3V DC (CR2025 lithium battery 1piece.)
Transmitting Signal Modulation Frequency	37.9kHz
Transmitting Distance	5m (min.)
No. of Keys	14keys (max.)
Operating Temperature Range	-20~55°C
Transmitting IC	Individual orders

## APPEARANCE AND OTHER SPECIFICATIONS

Item	Standard Specifications	Optional Specifications
Upper and Lower Cases	Molded base color (black)	_____
Key Top	Monochrome, rubber-coated resin.	Plural-color is available at option.
Window (LED part)	None	_____
Nameplate	Polycarbonate (Design is individual specification.)	_____
Back Label	None	Back label is available.
Infrared LED	1 piece	_____
Packing	Mitsumi standard packing	A previous arrangement specially.

## DIMENSIONS

